

430267

Technical Specification

Triac Dimmable Driver 28W-42W

General data

| | |
|------------------------------------|------------------------|
| Install Connector Type | Push Terminal |
| Input Cable | NO |
| Input Electrical Connection | Live Neutral Earth |
| Operating Temperature Range | -10 - +40 °C |
| Warranty | 5 Years |

Electrical data

| | |
|-----------------------------------|---------------|
| Wattage +/-10% | 28-42 W |
| Mains voltage | 220 - 240 V |
| Electrical protection | Class II |
| Driver Output | 30 - 40 V |
| Driver Output Current | 700 - 1050 mA |
| Control Gear Type CC or CV | CC |
| Dimmable | YES |
| Driver Brand | Lumineux |
| Nominal Frequency | 50/60 Hz |

Physical Data

| | |
|------------------|-------|
| IP Rating | 20 IP |
|------------------|-------|

| | |
|---------------|--------|
| Weight | 0.4 kg |
|---------------|--------|

Packaging

| | |
|---------------------------|---------------|
| Product EAN number | 5055379558091 |
|---------------------------|---------------|

| | |
|-------------------------------|--------|
| Packaging Inner Length | 180 mm |
|-------------------------------|--------|

| | |
|------------------------------|--------|
| Packaging Inner Width | 100 mm |
|------------------------------|--------|

| | |
|-------------------------------|-------|
| Packaging Inner Height | 75 mm |
|-------------------------------|-------|

Standards and Approvals

| | |
|--------------------------------------|----------------------|
| Manufactured In Accordance To | Available on Request |
|--------------------------------------|----------------------|
